


## Material Specifications:

VersiGrid™ MD.1.5


© 2018 VersiGrid™ Bonner MT USA  
All rights reserved

Material:	100% Recycled Plastic Black
Standard Color:	Black
Dimensions:	12" x 12" x 1.5"
Porosity:	85% Open, before filling
Cell size:	2.24" avg. (5.69cm)
Wall thickness I/O:	0.125" (0.3175cm)
Weight/piece:	1.5 lbs./piece (0.68 kg/piece)
Weight/assembly mat:	18 lbs/12 piece mat (8.16 kg/12 piece mat)
Compressive strength:	>20 UStons/ft <sup>2</sup> (215 metric tons/m <sup>2</sup> )
Load Capacity:	>20 UStons/axle (18.14 MT/axle)
Stability of Shape:	-58°F to +194°F (-50°C to +90°C)
Chemical Resistance:	Resistant against acid and leaching compounds, alcohol, or similar solvents.
Coverage/piece:	1.00/ft <sup>2</sup> (0.09 m <sup>2</sup> )
Coverage/assembly mat:	12.00/ft <sup>2</sup> (1.11 m <sup>2</sup> )
Installation rate:	up to 1,000 ft <sup>2</sup> /man-hour




## Typical Grid Tile

no scale



## Pre-assembled Mats

no scale



## Typical Section A

no scale